

Specification:

Ammonia Wrap-Around pipe Marker



Specifications:

- Material: Semi-rigid Vinyl
 - .015" (Style WAA - WB)
 - .030" (Style WC - WH)
- Temperature Range: -40°F to 180°F
- Compliance: Meets IIAR standards for letter size, length of marker, and legend information
- Life Expectancy:
 - Indoor: Indefinite
 - Outdoor: 5-7 years

Kolbi Style	Pipe OD (Includes Insulation)	Letter Size	Marker Length	Shape
AWAA	Less than 3/4"	1/2"	8"	Coiled
AWA	3/4" to 1"	1/4"	8"	Coiled
AWB	1-1/8" to 2-1/4"	3/4"	8"	Coiled
AWC	2-1/2" to 3-1/4"	1-1/4"	12"	Coiled
AWD	3-3/8" to 4-1/2"	1-1/4"	12"	Coiled
AWE	4-5/8" to 5-7/8"	1-1/4"	12"	Coiled
AWF*	6" to 7-7/8"	1-1/4"	12"	Flat*
AWG*	8" to 10"	2-1/2"	24"	Flat*
AWH*	Over 10"	3-1/2"	32"	Flat*

Order #	Legend	Abbr.	State	Pressure
A1	BOOSTER DISCHARGE	BD	VAP	LOW
A2	CONDENSER DRAIN	CD	LIQ	HIGH
A3	DEFROST CONDENSATE	DC	LIQ	HIGH
A4	ECONOMIZER SUCTION	ES	VAP	LOW
A5	EQUALIZER	EQ	VAP	HIGH
A6	FOUL GAS	FG	VAP	LOW
A7	HIGH PRESSURE LIQUID	HPL	LIQ	HIGH
A8	HIGH STATE DISCHARGE	HSD	VAP	LOW
A9	HIGH STATE SUCTION	HSS	VAP	LOW
A10	HIGH TEMP RECIRCULATED LIQUID	HTRL	LIQ	LOW
A11	HIGH TEMP RECIRCULATED SUCTION	HTRS	LIQ/ VAP	LOW
A12	HIGH TEMP SUCTION	HTS	VAP	LOW
A13	HOT GAS	HG	VAP	HIGH
A14	LIQUID DRAIN	LD	LIQ	LOW

Order #	Legend	Abbr.	State
A16	LIQUID INJECTION COOLING	LIC	LIQ
A17	LIQUID TRANSFER	LT	LIQ
A18	LOW STAGE SUCTION	LSS	VAP
A19	LOW TEMP RECIRCULATED LIQUID	LTRL	LIQ
A20	LOW TEMP RECIRCULATED SUCTION	LTRS	LIQ/ VAP
A21	LOW TEMP SUCTION	LTS	VAP
A22	MEDIUM TEMP RECIRCULATED LIQUID	MTRL	LIQ
A23	MEDIUM TEMP RECIRCULATED SUCTION	MTRS	LIQ/ VAP
A24	MEDIUM TEMP SUCTION	MTS	VAP
A25	PUMP OUT	PO	
A26	PURGE LINE	PL	VAP
A27	RELIEF VENT	RV	
A28	RELIEF VENT	RV	VAP LIQ/ VAP