

Product Specifications

Standard Sign Examples



OSHA Standard - Bilingual



Physical Properties

Standard Sizes	7"x10", 10"x14", 14"x20", 18"x24" (othe sizes available upon request)
Installation Options	Adhesive backing, Holes in corners, Holes in corners and adhesive backing
Hole Dimensions	3/16" standard hole size
Service Temp	-40°F to 180°F (-40° C to 82°C), Up to 300°F (149°C) with rivet mounting
Water Resistance	Excellent
Finish	Semi-gloss
Material Properties	.040" or .080" Aluminum
Material Options	Dry erase laminate available , Reflective Materail, UV laminate available
Standard Heading Options	Danger, Warning, Notice, Caution
Accessories Options	Zip ties, Stainless Steel Beaded Chain, Brass beaded chain
Color Options	Full color custom print available
Storage Stability	Indefinite when stored at 70°F (21°C) and 50% RH
Outdoor Durability	4 to 6 years, UV Resistant option available for outdoor use
Chemical Resistance:	Resistant to Acids, Alkalis and Salts
Equivalent To:	Brimar Aluminum Safety Signs, Seton Aluminum OSHA Signs, Marking Services Aluminum Safety Signs

Project

DATE _____
MM DD YYYY

JOB _____

CONTRACTOR NAME _____