

Manufactured for specialized projects requiring the high durability and properties of stainless steel. The plates are laser etched Anodized Aluminum Plates are highly durable and available in 8 color combinations. They are laser etched creating highly detailed and lasting images. Excellent for smaller text, drawings, images or bar codes. Creating highly detailed and lasting images. Excellent for smaller text, drawings, images or bar codes.

Anodized Aluminum Nameplate Examples

• SAMPLE •

Nameplate size: 1 x 4 in
0.5 inch text size (sized to fit also available)

RTU-1
ROOFTOP UNIT
DRAWING R1004

These images are for approximate representation only.

Nameplate Size: 2 x 4 in
Row one - 3/4 inch text size
Row two - 3/8 inch text size
Row three - 1/4 inch text size

PANEL
A
CONTROLS SUPPLY
TO GENERATOR 2

Nameplate Size: 2 x 3 in
Row one - 3/8 inch text size
Row two - 3/4 inch text size
Row three and four - 3/16 inch text

SHUT-OFF
VALVE

Nameplate Size: 2.5 x 4 in
1/2 inch text size (sized to fit also available)

Nameplate Sizes	
3/4 x 2-1/2 in (19 x 64 mm)	3 x 5 in (76 x 127 mm)
1 x 2 in (25 x 51 mm)	3 x 6 in (76 x 152 mm)
1 x 3 in (25 x 76 mm)	4 x 6 in (102 x 152 mm)
1 x 4 in (35 x 102 mm)	4 x 8 in (102 x 203.2 mm)
1-1/2 x 4 in (38 x 102 mm)	4 x 12 in (102 x 304.8 mm)
2 x 3 in (51 x 76 mm)	6 x 12 in (152 x 304.8 mm)
2 x 4 in (51 x 102 mm)	8 x 12 in (203.2 x 304.8 mm)
2-1/2 x 4 in (64 x 102 mm)	12 x 12 in (304.8 x 304.8 mm)
2 x 6 in (51 x 152 mm)	12 x 18 in (304.8 x 457.2 mm)
3 x 4 in (76 x 102 mm)	Custom Size Required

Text Sizes	Number of Lines			
	1	2	3	4
Sized to fit nameplate				
3/16 in (4.7625 mm)				
1/4 in (6.35 mm)				
3/8 in (9.525 mm)				
1/2 in (12.7 mm)				
3/4 in (19.05 mm)				
1 in (25.4 mm)				
Other				

Mounting Options	
Corner Holes	
Holes Centered Left & Right	
Top Corner Holes	
Holes Centered Top & Bottom	
Adhesive Backing	May combine with any option above

Codes	
Barcode	
QR Code	

Colors	
WHITE/BLACK	
WHITE/GOLD	
WHITE/RED	
WHITE/BLUE	
WHITE/ORANGE	
WHITE/GREEN	
WHITE/ALUMIN	
BLACK/ALUMIN	

Installation Instructions	For adhesive backing applied to a clean dry surface above 50°F (10°C)
Service Temp	-200°F to 1400°F (-128°C to 760°C)
Water Resistance	Excellent
Finish	Brushed Gloss
Material Properties	20 Gauge (0.032"/0.812 mm thick) Anodized Aluminum
Text	Laser Etched White Finish, *Digital print for black text
Installation Options	Adhesive backing, Holes and Adhesive Backing, Magnetic backing
Hole Options	one hole each side centered, holes in corners, holes in top corners
Adhesive Properties	4-mil Acrylic Adhesive
Storage Stability	Indefinite when stored at 70°F (21°C) and 50% RH
Outdoor Durability	Excellent
Chemical Resistance	Excellent
Equivalent To	Seton Laser Etched Anodized Aluminum, Marking Services Inc. Anodized Aluminum Tags, Brady Anodized Aluminum Valve Tags

DATE	/	MM	/	DD	/	YYYY	JOB
CONTRACTOR NAME							