

Reflective Firestop signs identify where firestop materials have been applied and prevent the removal of the material. You can either order our standard OSHA Firestop Warning Sign or you can order a custom sign with the installing contractor's information on it.



Sizing	Overall Dimensions
Style 1	4" High x 6" Wide
Style 2	7" High x 10" Wide
Style 3	10" High x 14" Wide

Installation Instructions	Applied to a clean dry surface above 32°F (0°C)
Service Temp	-40°F to 176°F (-40°C to 80°C)
Water Resistance	Good, Product has passed submersion tests
Finish	High Gloss Engineer Grade Reflective
Material Properties	6 Mil vinyl with pressure sensitive adhesive backing
Adhesive Properties	Aggressive permanent acrylic adhesive
	Stainless Steel 54 oz/in (594 N/m), Acrylic 56 oz/in (616 N/m)
	Glass 53 oz/in (599 N/m), Polypropylene 51 oz/in (561 N/m) Expected Shear: 5 hours, Tack gm (740)
Ink Properties	Inks resistant to fading with UV exposure, Semi-Gloss Finish
Storage Stability	2 years stored at 70°F (21°C) and 50% RH
Outdoor Durability	4 to 6 years
Abrasion Resistance	Good
Chemical Resistance	Resistant to Acids, Alkalies and Salts
Equivalent To	My Safety Signs Firestop Signage, Seton Safety Signage, Safetysigns.com Safety Signs

DATE	/	MM	/	DD	/	YYYY	JOB	
CONTRACTOR NAME _____								