Product Specifications

Kolbi Firewall Signs are made of a heavy-duty engineer grade 6mil vinyl with a high-strength adhesive to ensure the longevity of the product in its intended environment. In addition to being compliant with IBC 703.7 2018 Kolbi Firewall Signs can have important information added to the bottom of the sign such as; installing contractor info, building engineer contact information, and the Fire/Smoke barrier that is in place.

TOP LINE 3" TEXT

BOTTOM LINE 3/8" TEXT

PROJECT AND CONTRACTOR INFORMATION

1 HOUR
FIRE/SMOKE BARRIER

PROTECT ALL OPENINGS AND PENETRATIONS

ATTENTION: WORKERS CUTTING INTO WALL CONTACT BUILDING ENGINEER UPON COMPLETING WORK

Building Engineer Phone: _____   Product Installed: _____

Installing Contractor: _____   Installing Contractor Phone: _____

12"

16"

Sizing	
Overall Dimensions	12" High x 16" Wide
Rating Text Size	3"
Barrier Type Text Size	3/8"

Physical Properties

Standards Met	IBC (International Building Code) 703.7 2018
Installation Instructions	Applied to a clean dry surface above 32°F (0°C)
Service Temp	-40°F to 176°F (-40°C to 80°C)
Water Resistance	Good, Product has passed submersion tests
Finish	High Gloss
Material Properties	6 Mil vinyl with pressure sensitive adhesive backing
Adhesive Properties	Aggressive permanent acrylic adhesive
	Stainless Steel 54 oz/in (594 N/m), Acrylic 56 oz/in (616 N/m)
	Glass 53 oz/in (599 N/m), Polypropylene 51 oz/in (561 N/m) Expected Shear: 5 hours, Tack gm (740)
Ink Properties	Inks resistant to fading with UV exposure, Semi-Gloss Finish
Storage Stability	2 years stored at 70°F (21°C) and 50% RH
Outdoor Durability	4 to 6 years
Abrasion Resistance	Good
Chemical Resistance	Resistant to Acids, Alkalis and Salts
Equivalent To	Firewallsigns.com Firewall Sign, My Saftey Sign Firewall Sign, Seton Firewall Sign

Project

DATE _____ / _____ / _____
       MM   DD   YYYY

JOB _____

CONTRACTOR NAME _____