KOLBI PIPE MARKER CO.

PRODUCT SPECIFICATION SHEET

Engraved Plastic Nameplates

Product Specifications

Kolbi Engraved Nameplates are designed to meet exact project requirements. These highly durable plates are available in the most commonly used sizes or custom-made to meet a specific need. There are five standard materials, all with beveled edges for a precise and professional look. Precision engraving equipment produces the exact letter size and font needed for optimal viewing from any distance. Ability to vary letter size by line creates plates that are easier to read and meet exact project specifications.

Engraved Plastic Nameplate Examples



Nameplate size: 1 x 4 in
0.5 inch text size (sized to fit also available)



Nameplate Size: 2 x 4 in
Row one - 3/4 inch text size
Row two - 3/8 inch text size
Row three - 1/4 inch text size



Nameplate Size: 2 x 3 in
Row one - 3/8 inch text size
Row two - 3/4 inch text size
Row three & four - 3/16 inch text size



Nameplate Size: 2.5 x 4 in
1/2 inch text size (sized to fit also available)

These images are for approximate representation only.

Nameplate Sizes			
☐	3/4 x 2-1/2 in (19 x 64 mm)	☐	3 x 5 in (76 x 127 mm)
☐	1 x 2 in (25 x 51 mm)	☐	3 x 6 in (76 x 152 mm)
☐	1 x 3 in (25 x 76 mm)	☐	4 x 6 in (102 x 152 mm)
☐	1 x 4 in (35 x 102 mm)	☐	4 x 8 in (102 x 203.2 mm)
☐	1-1/2 x 4 in (38 x 102 mm)	☐	4 x 12 in (102 x 304.8 mm)
☐	2 x 3 in (51 x 76 mm)	☐	6 x 12 in (152 x 304.8 mm)
☐	2 x 4 in (51 x 102 mm)	☐	8 x 12 in (203.2 x 304.8 mm)
☐	2-1/2 x 4 in (64 x 102 mm)	☐	12 x 12 in (304.8 x 304.8 mm)
☐	2 x 6 in (51 x 152 mm)	☐	12 x 18 in (304.8 x 457.2 mm)
☐	3 x 4 in (76 x 102 mm)	☐	Custom Size Required

Colors	
☐	WHITE/BLACK
☐	BLACK/WHITE
☐	WHITE/RED
☐	WHITE/BLUE
☐	BLACK/ORANGE
☐	WHITE/GREEN
☐	RED/WHITE
☐	WHITE/GREY
☐	BLACK/YELLOW

Text Sizes	Number of Lines 1	2	3	4
Sized to fit nameplate	☐	☐	☐	☐
3/16 in (4.7625 mm)	☐	☐	☐	☐
1/4 in (6.35 mm)	☐	☐	☐	☐
3/8 in (9.525 mm)	☐	☐	☐	☐
1/2 in (12.7 mm)	☐	☐	☐	☐
3/4 in (19.05 mm)	☐	☐	☐	☐
1 in (25.4 mm)	☐	☐	☐	☐
Other	☐	☐	☐	☐

Barcode Option

☐ 

Materials	
☐	1/16" 2-ply Plastic
☐	1/16" Outdoor Material
☐	1/16" 3-Ply Material
☐	1/8" 2-ply Plastic
☐	1/8" Outdoor Grade Plastic
☐	1/8" 3-ply Material

Mounting Options	
☐	Corner Holes
☐	Holes Centered Left & Right
☐	Top Corner Holes
☐	Holes Centered Top & Bottom
☐	Adhesive Backing

Physical Properties

Installation Instructions	For adhesive backing applied to a clean dry surface above 50°f (10°c)
Service Temp	-40°F to 200°f (-40°c to 93°c)
Water Resistance	Good
Finish	Matte
Material Properties	Impact acrylic
Material options	1/16"(1.6mm), 1/8"(3mm) , 3ply (double sided)
UV resistant option	UV resistant option available for some colors
Installation Options	Adhesive backing, holes and adheisve backing, magnetic backing
Hole Options	One hole each side centered, holes in corners, holes in top corners
Adhesive Properties	4-Mil acrylic adhesive, adhesive rated from -40°F to 175° F (-40°C to 79.45°C)
Storage Stability	Indefinite when stored at 70°f (21°c) and 50% rh
Outdoor Durability	4 - 6 Years (UV Resistant Material 15+ years)
Chemical Resistance	Resistant to acids, alkalis and salts
Equivalent To	Seton Setonflex, Brimar Briply, Marking Services Inc. Ms-264, Brady Engraved Plastic Namepates

Project

DATE _____ / _____ / _____ JOB _____
MM DD YYYY

CONTRACTOR NAME _____